

Digital Migration Radio P3D Series

Pocket-size Design

Micro USB Charging

Dual Modes (Analogue & Digital)

Superior Audio





P3D5X

Pocket-size Design

Micro USB Charging



Applications



Sport Events



Hospitality



Retail



Warehouse



P3D6X

Superior Audio

Dual Modes (Analogue & Digital)

- Pocket-size design and easy to carry
- Four programmable buttons
- Micro USB port for easy charging
- Radio more compact through creative antenna design
- In digital mode, radio operates up to 12 hours using a duty cycle of 5-5-90
- Dual mode ensures smooth migration from analogue to digital
- Voice communication includes private, group and all call
- Work and user groups can be configured with unique CTCSS/CDCSS to prevent unwanted conversations on the same frequency
- Radios can be enabled to continuously scan each analogue and digital channel
- Supports messaging with up to 64 characters
- Supports a one touch feature for pre-programmed text messages and voice calls
- High quality speaker for clear audio
- Cost-effective digital experience

Accessories

Versatile Accessories for Specific Tasks



PD35X Belt Clip



PD36X Belt Clip




Micro USB
Power Adapter
(5V/1A)



Programming Cable



BL2009



Nylon Strap



P3D5X

P3D6X

Specifications

General		
Frequency Range	UHF: 400-440MHz, 430-470MHz*, 446MHz*	
Channel Capacity	256	
Channel Spacing	25/12.5KHz	
Operating Voltage	3.7V	
Battery	2000mAh (Li-Ion)	
Battery Life (5/5/90)	Digital: approximately 12 hours Analogue: approximately 10 hours	
Weight	160g	
Dimensions	123 x 55 x 23mm (PD35X) 106 x 54 x 23mm (PD36X)	
Frequency Stability	±0.5ppm	
Antenna Impedance	50Ω	
Receiver		
Sensitivity (Digital)	0.22µV/BER 5%	
Sensitivity (Analogue)	0.22µV (Typical) (12dB SIN AD) 0.4µV (20dB SIN AD) 0.22µV (12dB SIN AD)	
Adjacent Selectivity	TIA-603	60dB @ 12.5KHz/70dB @ 25KHz
	ETSI	60dB @ 12.5KHz/70dB @ 25KHz
Spurious Response Rejection	TIA-603	70dB @ 12.5/25KHz
	ETSI	70dB @ 12.5/25KHz
Inter-modulation	TIA-603	70dB @ 12.5/25KHz
	ETSI	65dB @ 12.5/25KHz
Hum & Noise	40dB @ 12.5KHz 45dB @ 25KHz	
Rated Audio Power Output	0.4W	
Rated Audio Distortion	<5%	
Audio Response	+1 ~ -3dB	
Conducted Spurious Emission	<-57dBm	

P3D5X/P3D6X, X=2, 5, 6 or 8, model number varies geographically. For details, please contact our regional sales representatives.

Transmitter	
RF Power Output	UHF High power: 3W UHF Low power: 1.5W
FM Modulation	11K0F3E @ 12.5KHz 16K0F3E @ 25KHz
4FSK Digital Modulation	12.5KHz Data Only: 7K60FXD 12.5KHz Data & Voice: 7K60FXW
Conducted/Radiated Emission	-36dBm <1GHz, -30dBm >1GHz
Modulation Limiting	±2.5KHz @ 12.5KHz ±5.0KHz @ 25KHz
FM Hum & Noise	40dB @ 12.5KHz 45dB @ 25KHz
Adjacent Channel Power	60dB @ 12.5KHz, 70dB @ 25KHz
Audio Response	+1 ~ -3dB
Audio Distortion	≤3%
Digital Vocoder Type	AMBE++ or SELP
Digital Protocol	ETSI-TS102 361-1,-2,-3
Environmental	
Operating Temperature	-30°C ~ +60°C
Storage Temperature	-40°C ~ +85°C
ESD	IEC 61000-4-2 (Level 4) ±8kV (Contact) ±15kV (Air)
Dustproof & Waterproof	IP54 Standard
Humidity	Per MIL-STD-810 C/D/E/F/G Standard
Shock & Vibration	Per MIL-STD-810 C/D/E/F/G Standard

* 430-470MHz, 446MHz, coming soon. 446MHz only CE certified.
All specifications are subject to change without notice due to continuous development.



Long Range Systems UK Limited

Address: Link House, Leek Road, Milton, Stoke on Trent
Staffordshire, ST2 7AH **Tel:** 01782.537000
Http: //www.pager.co.uk